

NPFSR-K4C31AD

3X 1 WÄ P G 3 1
X 3NO+1NC

K

1002

■

■

■

■

■



Technical Specifications

Rated Voltage	24V AC/DC
Rated Current	0.85 ~ 1.1
Rated Frequency	50Hz ~ 60Hz
Rated Power	≤ 2.2W/24V DC, ≤ 5.4VA/24V AC
Rated Load	≤ 50mA/24V DC
Rated Resistance	≤ 15Ω
Rated Temperature	
Rated Resistance	2 ~ 20kΩ
Rated Voltage	3NO+1NC
Rated Power	
Rated Power	AgSnO ₂ +0.2μmAu
Rated Power	AC-15: 5A/230V, DC-13: 5A/24V
Rated Power	10A gL/gG(NO), 6A gL/gG(NC)
Rated Power	≤ 100ms
Rated Power	: ≤ 30ms, : ≤ 100ms
Rated Power	: ≤ 30ms, : ≤ 100ms
Rated Power	20ms
Rated Power	IEC/EN 60947, IEC 61326-3-1, IEC/EN 61000-6-2, IEC/EN 61000-6-4
Rated Power	250V AC
Rated Power	6000V(1.2/50us)
Rated Power	1500V AC, 1 min
Rated Power	IEC 60947-1
Rated Power	10Hz ~ 55Hz, 0.35mm
Rated Power	III
Rated Power	2
Rated Power	IP20
Rated Power	-20°C ~ +60°C
Rated Power	-40°C ~ +80°C
Rated Power	≤ 2000 m
Rated Power	10×10 ⁶ cycles

Environmental Specifications

Rated Power	PLd, ISO 13849
Rated Power	Cat.3, ISO 13849
Rated Power	20, ISO 13849
Rated Power	99%, ISO 13849
Rated Power	162, ISO 13849
Rated Power	68, ISO 13849
Rated Power	SIL2, IEC 61508
Rated Power	SIL CL2, IEC 62061
Rated Power	1, IEC 62061
Rated Power	≥ 99%, IEC 62061
Rated Power	1.65×10 ⁻⁵ /PTI=20年, IEC 61508
Rated Power	1.91×10 ⁻¹⁰ 1/h, IEC 62061
Rated Power	0, IEC 60204